



Wheel sensors.
Rail switches.

Wheel sensors

Rail switches

Applications

- >> Train locating
- >> Direction detection
- >> Axle counting

Product advantages

- >> Non-contact and non-wear activation by the wheel
- >> Maintenance-free with high durability
- >> No need to adjust anything in the entire rail and wheel range prone to wear
- >> Affixing the switch does not weaken the rail
- >> Robust and weatherproof
- >> Compact dimensions
- >> Not affected by rail currents, harmonics, radio waves, etc.



Inductive sensors which detect the metal mass of the rail wheel flange, using them to generate electric impulses

The designation 'wheel sensor' originates in the sensor switches which PINTSCH TIEFENBACH has been developing and manufacturing since starting its business operations in the 1950s, which are activated by non-contact magnets (magnetic switches) or by metal masses, so-called inductive proximity switches. The latter were enhanced for use as wheel detectors in the railway industry, and because they are affixed to rails for this application, are referred to as wheel sensors. PINTSCH TIEFENBACH's extensive experience in manufacturing sensors was decisive for the product design, which has remained in use until today.

Depending on the application, a distinction is made between single wheel sensors for vehicle detection and switching tasks, and double wheel sensors for direction detection, axle counting and speed measurements.

PINTSCH TIEFENBACH's expertise in the manufacture of wheel sensors is based on more than 30 years of experience in which these products have been consistently enhanced and improved. The customer receives a product which has proven its high level of operational reliability in a multitude of applications, but has primarily been used as an axle counting points, satisfying the requirements of the user optimally.



When it comes to the wheel sensors, PINTSCH TIEFENBACH provides its customers with – in every respect – customised components for evaluating and subsequent processing of the sensor signals, providing users with support when configuring and installing the components.

This involves providing special switching amplifier modules employing Euro rack technology or isolating amplifiers in compact housing configurations for installation on DIN- rails, used for processing signals.

A patented process of operation by using a constant current source allows the wheel sensors – in combination with these modules – to realize a precise and very reliable switching performance even at higher speeds and extensive cable lengths.



Types / Applications

Type	Single wheel sensor	Double wheel sensor	Application			Vmax	Interface according to DIN 19234 (NAMUR)	Special feature
			Train location	Direction detection	Axle counting			
N59-1R-200-45	X		X			≤60 km/h	X	
N59-1R-200-40	X		X			≤350 km/h		
N59-116l-200-45	X		X			≤350 km/h		Complete with integrated isolating amplifier
N59-116vl-200-45	X		X			≤350 km/h		Integrated isolating amplifier, impulse extension 4s
2N59-1R-200-45		X	X	X	X	≤60 km/h	X	DB material number: 00117857
2iNX59-1R-200-45		X	X	X	X	≤60 km/h	X	Intrinsically safe, explosion proof in accordance with Directive 94/9/EC [ATEX]
2N59-1R-200-40		X	X	X	X	≤350 km/h		
2N59-1R-400RE-40		X	X	X	X	≤350 km/h		Only available with PINTSCH TIEFENBACH axle counting systems



02/2013 V01

PINTSCH TIEFENBACH US, Inc.
810 Skyline Drive
Marion, Illinois 62959

Phone (618) 993-8513
Fax (618) 993-8403

info@pintschtiefenbach.us.com
www.pintschtiefenbach.us.com

PINTSCH TIEFENBACH
A Schaltbau Company